



GXV340

Professionals rely on the GXV340 to deliver reliable, easy starting, fuel efficient performance, day in and day out.

INTRODUCTION

COMMON APPLICATIONS

The Honda GXV340 is used throughout Australia to power commercial lawn and garden equipment, including Ride-on lawn mowers.

As well as this, the GXV340 is often used to power Construction/Industrial Equipment, as well as heavy-duty Agricultural equipment.

There's enough guts in the GXV340 to power equipment such as Mini Loaders, and it's also used in Floor Cleaning applications.

FUEL EFFICIENT, HIGH OUTPUT OPERATION

The GXV340's precision camshaft design offers precise valve timing and optimal valve overlap for better fuel efficiency, and its Overhead Valve design supplies optimal power transfer.

It also incorporates a high compression ratio for better fuel efficiency, which is handy for your pocket - and the environment.

Precision engineered components result in lower vibration, and the GXV340 features Dual balancer shafts and a Ball Bearing-supported crankshaft for greater stability and smooth performance.

EXCEPTIONALLY QUIET

The GXV340 is exceptionally quiet for its size and output. This is in part due to its large capacity, multi-chamber exhaust system.

Its design incorporates a forged steel crankshaft and rigid crankcase, helical cut gears, and a sophisticated air intake system.

And it emits less mechanical noise due to lightweight, noise-reducing materials.

3 YEAR WARRANTY

Don't forget, all Honda GXV Engines are covered by a Honda 3 Year Domestic & Commercial Warranty.

The GXV340's simple operation is renowned, but if you need assistance or spare parts, Honda's got you covered.

With over 400 authorised Honda dealers around Australia, you'll never be on your own with a Honda engine.

OTHER FEATURES

Oil Alert, Cast iron cylinder sleeve, Dual element air cleaner, Large fuel tank, Large automotive type fuel cap, Easily accessible spark plug, and an Easy, convenient, heavy duty control box come standard.

It's built with high quality materials, fit, and finish, and has an automatic mechanical de-compression system.

EMISSION COMPLIANT

Applicable models meet the strictest world standards, contact Honda for more info

No catalyst necessary

AVAILABLE OPTIONS

Electric start

Spark arrester available

SPECS

SPECIFICATIONS

MODEL	GXV340
TYPE	Air-cooled 4-stroke OHV
BORE & STROKE	82 X 64 mm

DISPLACEMENT	337 cm ³
COMPRESSION RATIO	7.7:1
NET POWER	8.9 HP (6.6 kW) @ 3,600 rpm
CONTINUOUS RATED POWER	n/a
MAXIMUM NET TORQUE	21.6 Nm @ 2,500 rpm
IGNITION SYSTEM	Transistorised magneto
STARTING SYSTEM	Recoil/electric
COOLING SYSTEM	n/a
PTO SHAFT ROTATION	Counter-clockwise (from P.T.O. side)
FUEL CONSUMPTION AT RATED POWER	n/a
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Pressure and splash
RECOMMENDED OIL	n/a
OIL CAPACITY	1.1l
DIMENSIONS	433 x 382 x 406 mm
DRY WEIGHT	32.2kg
RRP	From AUD \$786.71 (includes GST)

[VISIT HONDA POWER EQUIPMENT WEBSITE](#)

For terms and conditions please visit http://about.hondampe.com.au/Terms_and_Conditions
The information in this document is valid as of 17/11/2014. For the most up to date information please visit <http://powerequipment.honda.com.au>