



GXV530

Professionals rely on the GXV530 to deliver reliable, easy starting, fuel efficient performance - day in, day out.

INTRODUCTION

COMMON APPLICATIONS

The Honda GXV530 is used throughout Australia to power commercial lawn and garden equipment, including Ride-on lawn mowers.

As well as this, the GX530 is often used to power Construction/Industrial Equipment, as well as heavy-duty Agricultural equipment.

There's enough directional power in the GX530 to also power equipment such as Mini Loaders, and it's also used in Floor Cleaning applications.

FUEL EFFICIENT, HIGH OUTPUT OPERATION

The GXV530's precision camshaft design offers precise valve timing and optimal valve overlap for better fuel efficiency, and its Overhead Valve design supplies optimal power transfer.

It also incorporates a high compression ratio for better fuel efficiency, which is handy for your pocket - and the environment.

Precision engineered components result in lower vibration, and the GXV530 features Dual balancer shafts and a Ball Bearing-supported crankshaft for greater stability.

EXCEPTIONALLY QUIET

The GXV530 is exceptionally quiet for its size and output. This is in part due to its large capacity, multi-chamber exhaust system.

Its design incorporates a forged steel crankshaft and rigid crankcase, helical cut gears, and a sophisticated air intake system.

And it emits less mechanical noise due to lightweight, noise-reducing materials.

3 YEAR WARRANTY

Don't forget, all Honda GXV Engines are covered by a Honda 3 Year Domestic & Commercial Warranty.

The GXV530's simple operation is renowned, but if you need assistance or spare parts, Honda's got you covered.

With over 400 authorised Honda dealers around Australia, you'll never be on your own with a Honda engine.

OTHER FEATURES

Oil Alert, Cast iron cylinder sleeve, Dual element air cleaner, Large fuel tank, Large automotive type fuel cap, Easily accessible spark plug, and an Easy, convenient, heavy duty control box come standard.

It's built with high quality materials, fit, and finish, and has an automatic mechanical de-compression system.

EASY STARTING

Heavy duty recoil starter

Automatic mechanical de-compression system

EMISSIONS COMPLIANT

Applicable models meet the strictest world standards, contact Honda for more info

No catalyst necessary

AVAILABLE OPTIONS

Electric start standard

Spark arrester available

SPECS

SPECIFICATIONS

MODEL	GXV530
TYPE	4-stroke, overhead cam, 90L V-twin, Vertical Shaft
BORE & STROKE	77 x 57 mm
DISPLACEMENT	530 cm ³
COMPRESSION RATIO	8.0:1
NET POWER	11.3kW (15.2HP) at 3,600 rpm
CONTINUOUS RATED POWER	7.3kW (9.8HP) at 3000 rpm
MAXIMUM NET TORQUE	34.2 Nm at 2,500 rpm
IGNITION SYSTEM	Transistorised magneto ignition
STARTING SYSTEM	Recoil with Electric or Electric Starter
COOLING SYSTEM	Forced-air
PTO SHAFT ROTATION	Counter-clockwise (from P.T.O. side)
FUEL CONSUMPTION AT RATED POWER	3.9 L/h at 3,000 rpm
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Pressure and splash
RECOMMENDED OIL	10W/30 API SG
OIL CAPACITY	1.05l
DIMENSIONS	456 x 427 x 331 mm
DRY WEIGHT	32.3kg
RRP	From AUD \$1,396.66 (includes GST)

VISIT HONDA POWER EQUIPMENT WEBSITE

For terms and conditions please visit http://about.hondampe.com.au/Terms_and_Conditions

The information in this document is valid as of 17/11/2014. For the most up to date information please visit <http://powerequipment.honda.com.au>